

MICHELIN PRIMACY 3

THE PERFECT COMBINATION OF SAFETY & LONGEVITY



MICHELIN Primacy 3, intended for luxury and top-of-the-range future classic saloons

**Voted
BEST
TYRE**
in its category
in 2015 and 2018
(2)



• EXCELLENT BEHAVIOUR ON WET ROADS

Drive safely even in the rain thanks to the combination of self-locking sipes and a patented rubber compound providing excellent performances on wet roads.⁽¹⁾
A premium tyre for premium performances.

• VERY LONG LIFE

The life of the MICHELIN Primacy 3 tyre has been improved thanks to a rubber compound that is highly resistant to abrasion and an optimized ground contact patch that spreads pressure and heat in the tyre more evenly. Voted best tyre in its category by the ADAC in 2015 and 2018⁽²⁾

⁽¹⁾ Braking efficiency on wet surfaces: The MICHELIN Primacy 3 tyre is graded A on the European label for grip on wet roads.

⁽²⁾ The MICHELIN Primacy 3 tyre obtained the best grade for longevity during the comparative test performed by the ADAC, in the dimension 205/55 R16 91V, published in February 2015 and February 2018.

classic.michelin.com



Technical characteristics

Tube type or Tubeless	Load/speed index	Cross-section width	External diameter	Rolling circumference	Rim dim. (min., measured, max.)
TL	88V	205	621	1952	5,5 6,0 7,0

Can be fitted to the following vehicles

Alfa Romeo	147, 164, Alfa GT, GTV, Spider
Chevrolet	Rezzo
Chrysler	Es, Stratus
Citroën	C3 Picasso, Xm
Daewoo	Rezzo
Fiat	Croma, Idea, Linea, Marea, Multipla
Ford	B-Max, Fiesta, Focus, Fusion, Mondeo, Tourneo, Transit
Honda	Accord, Civic
Hyundai	Elantra
Kia	Carens, Cerato
Lancia	Musa, Thema
Mazda	323, 626, Xedos
Mitsubishi	Carisma, Galant, Lancer
Nissan	200, Almera, Bluebird, Cube, Primera
Vauxhall	Astra, Calibra, Corsa, Vectra
Peugeot	505
Renault	Laguna, R25, Safrane, Scenic
Rover	600, 25 Streetwise
Saab	900
Subaru	Legacy
Toyota	Avensis, Camry, Celica, Corolla, Corolla Verso
Volkswagen	Golf
Volvo	240, 740, 760, 850, S40, V40, S70, V70

Technical characteristics

Tube type or Tubeless	Load/speed index	Cross-section width	External diameter	Rolling circumference	Rim dim. (min., measured, max.)
TL	91W	205	621	1952	5,5 6,0 7,5

Can be fitted to the following vehicles

Alfa Romeo	156, Alfa GT
Audi	80,100, A3, A4, A6, Cabriolet, Coupé, Quattro
BMW	Serie 3, Z3,
Chevrolet	Aveo, Beretta
Chrysler	Le Baron, Saratoga,
Citroën	Xantia, Xm
Daewoo	Leganza
Ford	Cougar, Galaxy
Honda	Legend
Hyundai	Sonata
Kia	Carens, Magentis
Lancia	Kappa, Lybra
Mazda	5, 626
Mercedes	200, 220, 230, 250, 260, 280, 300, 320, 400, Classe C, Classe CLK,SLK, Classe E
Mitsubishi	Galant
Morgan	Plus 4, Roadster
Vauxhall	Speedster, Vectra
Peugeot	406, 605
Renault	Laguna, R25, Safrane
Rover	800
Saab	9000
Seat	Alhambra
Skoda	Octavia
Subaru	Legacy
Volkswagen	Golf, Jetta, Passat, Sharan, Touran
Volvo	240, 780

Technical characteristics

Tube type or Tubeless	Load/speed index	Cross-section width	External diameter	Rolling circumference	Rim dim. (min., measured, max.)
TL	100W	233	682	2143	6,5 7,0 8,5

Can be fitted to the following vehicles

Alpina	B12
Audi	A8
BMW	Serie 7
Cadillac	Seville
Daihatsu	Terios
Ford	Ka, Kuga
Hyundai	Tucson
Kia	Sportage
Mercedes	420, 500, 600, Classe CL, Classe S
Suzuki	Vitara
Toyota	RAV 4 II
Volkswagen	Phaeton